

28mm CARTRIDGES

NEW STANDARD RANGE

Sedal has developed a new 28mm range of cartridges, allowing to keep the slim design of a 25mm cartridge but with the robustness of a 35mm.



FEATURING

SN-28

Slim design & higher flow rate

The SN-28 cartridge provides a slim design capability but not as thin as 25mm cartridges, resulting in an interesting intermediate performance in between 35mm and 25mm taps. The manufacturer can keep a slim design but can obtain a higher flow rate and a robust comfort of operations.



28MM CARTRIDGES
NEW
STANDARD

RECOMMENDED APPLICATIONS



WASHBASINS

Specially designed for washbasins.



KITCHENS

Suitable for use in kitchens.

Soft movement

It features soft operational movement thanks to a clutched ceramic movement and high grade ceramics. Up to 40% softer lever operation than standard cartridges thanks to this operation design.

TECHNICAL SPECIFICATIONS

	SN-28	EX-28	EX-28 TOP
Nut torque pitch M1.5	7-8Nm	8 Nm	7-8Nm
Opening angle	23°	22°	22°
Rotation angle	100°	90°	90°
Working pressure (recommended)	1 - 5 bar	1 - 5 bar	1 - 5 bar
Burst pressure	>35 bar	>35 bar	>35 bar
Life cycle- x2 ASME x2 EN 817 NF-077 U3 x2 GB-18145	500,000 cycles	500,000 cycles 140,000 cycles	1,000,000 cycles 140,000 cycles 175,000 cycles 140,000 cycles
Sensitivity (r=45mm)	>10 mm	10° - 12° angle	12° angle
Fidelity	<5°C	3 °C	<5°C

Tested with proprietary fixtures at SEDAL lab. (1) Considering restrictor & faucet body type

EX-28



Compact design

Compact 28 mm cartridge allows the manufacturer to create minimalistic faucets without giving up the high-performance features of the cartridges. With EX-28 you can find a 35mm performance in a 28mm body.

EX-28 TOP



THE BEST IN CLASS

The EX-28 cartridge provides a slim design capability resulting in a interesting intermediate way between 35 mm and 25 mm taps. It features soft operational movement thanks to a high grade ceramics and allows to aim for the most demanding standards, like NF-077 ECAU and low noise levels.

RECOMMENDED APPLICATIONS



CONCEALED WASHBASINS

Specially designed for washbasins.



CONCEALED SHOWERS

Specially designed for one outlet showers.



CONCEALED KITCHENS

Suitable for use in kitchens.

RECOMMENDED APPLICATIONS



CONCEALED WASHBASINS

Specially designed for washbasins.



CONCEALED SHOWERS

Specially designed for one outlet showers.




CONCEALED KITCHENS

Suitable for use in kitchens.

TECHNICAL SPECIFICATIONS

	SN-28	EX-28	EX-28 TOP
Constant 63 °C & 50 °C (6 l/min - 3 l/min)	<4°C - <6°C	<4°C - <6°C	<4°C - <6°C
Max. hot water*	90 °C	90 °C	90 °C
Operation Torque			
Open-close	0.15-0.30 Nm	0.15-0.30 Nm	0.15-0.30 Nm
Turn left-right	0.15-0.35 Nm	0.25-0.35 Nm	0.15-0.30 Nm
Flow rate at 3 bar			
at 0.5 bar	8.6 l/min	5.7 l/min	-
at 1 bar	12.2 l/min	12 l/min	-
at 3 bar	21.2 l/min	20.3 l/min	13.9 l/min
at 5 bar	27.5 l/min	25.8 l/min	-

Tested with proprietary fixtures at SEDAL lab. (1) Considering restrictor & faucet body type



Get access to the complete and
latest product technical data!



SEDAL GROUP

Polígono Industrial Can Sunyer · C/Química, 2-12
E-08740 Sant Andreu de la Barca (Barcelona) · Spain
Tel. +34 93 680 33 00 · Fax +34 93 680 33 03
sedal@sedal.com · www.sedal.com