

Sedal

Headworks



The faucet's heart

Plastic Headworks

Plastic Headworks 90°

Ceramic headworks made from high strength technical plastic body, with a rotation angle of 90° suitable for lead-free applications.

10 Nm

Recommended
Installation torque
for plastic headworks

Certifications

KTW · ACS · NSF · WRAS°



Plastic Headworks 180°

Ceramic headworks made from high strength technical plastic body, with a rotation angle of 180° suitable for lead-free applications.

10 Nm

Recommended
Installation torque
for plastic headworks

Certifications

KTW · ACS · NSF · WRAS

OEM Headworks

We develop OEM headworks on demand according to the client's requirements in any material. We also adapt to the required external dimensions and features, such as 1/2", 3/4", or M18x1.5..

1.000.000

Life cycles headworks
on demand



Brass & Stainless Steel

Brass 90° & 180° Headworks

Ceramic headworks made from brass body, with a rotation angle of both 90° & 180°.

12 Nm

Recommended
installation torque
for brass headworks

Certifications

KTW · ACS · WRAS · NSF



Stainless Steel 90° Headworks

Ceramic headworks made from stainless steel body, with a rotation angle of 90°.

12 Nm

Recommended
installation torque
for brass headworks

Conventional Brass Headworks

Conventional headworks made from brass body.

Certifications

ACS · NSF



Sedal

Technical Specifications

Standard headworks specifications

	Plastic HW	Brass HW
Assembly Torque	8-10Nm	10-12Nm
Rotation angle	90° /180°	
Working pressure (recommended)	1 - 5 bar	
Pressure resistance ASME A112	35 bar	
Life cycle - EN 200	200.000 cycles	
ASME A112	500.000 cycles	
Max. hot water	90 °C	
Turn left-right	0.10÷0.20 Nm	



Get access to the complete and
latest product technical data!

Sedal

Sedal Group

Polígono Industrial Can Sunyer · C/Química, 2-12
E-08740 Sant Andreu de la Barca (Barcelona) · Spain

Tel. +34 93 680 33 00

sedal@sedal.com · www.sedal.com